



Wetroom areas

The best insulated wetroom board on the market!

Marmox Multiboards offer high thermal insulation, are fully waterproof and strong enough to support the heaviest of tiles. They can be fitted to floors, walls and ceilings to allow for a fully-waterproof area. With a range of thicknesses from 4mm to 60mm, Multiboards can be used to construct bath surrounds, steps or vanity units. Once fitted, just tape the joints with waterproof tape and they are ready to tile. There really is no easier or better alternative for wetroom areas.



- fully waterproof
- high thermal insulation
- holds up to 62kg/m²
- use as a construction board
- easy to cut with a saw or knife
- ready to receive tiles



Wetroom areas

What are Multiboards?

Marmox Multiboards are lightweight, easy to handle, insulated boards made of extruded polystyrene and coated on each side with a close woven fibreglass mesh embedded in a cement polymer mortar. Multiboards are fully waterproof and therefore do not allow any water to pass through them in the way expanded polystyrene boards do. They are ideal for use with Marmox Showerlay (floor level shower base).

Marmox Multiboard sizes

thickness (mm)	width (mm)	length (mm)	weight (kg)	R value
4	600	1250	1.81	0.10
6	600	1250	1.95	0.16
10	600	1250/2500	2.22/4.44	0.28
12.5	600	1250/2500	2.28/4.56	0.36
20	600	1250/2500	2.48/4.96	0.59
30	600	1250/2500	2.74/5.48	0.91
40	600	1250/2500	3.00/6.00	1.22
50	600	1250/2500	3.26/6.52	1.53
60	600	1250/2500	3.60/7.20	1.84

Technical data

Density	DIN 53420	36kg/m ³
Thermal Conductivity	DIN 52612	0.027 watt/mK
Thermal Conductivity (5 years)	DIN 52612	0.032 watt/mK
Compressive Strength	DIN 53421	3.0kg/cm ² (300kN/m ²)
Water Absorption (Immersion)	DIN 53428	0.02% by vol
Water Absorption (Capillary)	DIN 53428	Nil
Coefficient Of Linear Expansion		30 x 10 ⁻⁶
Flammability	DIN 4102	B1
	BS 476 Part 6,7	Class '0'

